

## AVC63-7, AVC63-7D, AVC63-7F Voltage Regulators





#### **Overview**


Enjoy proven, dependable, high performance with Basler Electric's AVC line. These extremely rugged and reliable regulators provide performance and functionality that revolutionized the modern analog voltage regulator market, and they are still unrivaled today. Others have attempted to imitate the AVC's features and functions, but only the AVC remains the total solution.

#### **Features**

- Integrated circuitry for compact size, simplicity, high reliability
- Extremely rugged
- Exciter field current 7 A continuous
- Regulation accuracy better than ±0.25% no-load to full-load
- Fast response
- Frequency compensation
- Built-in parallel droop compensation

#### **Benefits**

- Voltage regulation performance is constant over the entire operating temperature range without derating or degradation.
- Potted design allows installation in harsh environments.
- Reduce or eliminate expensive service calls because of the reliable, rugged construction.
- Integrated paralleling provides exceptional reactive load sharing with simple setup for quick commissioning.
- Volts per hertz limiting, overexcitation shutdown, provisions for external voltage adjustments, integrated paralleling provisions, and potted construction make the AVC line a good fit for most applications. It's the "universal" regulator that reduces inventory to one device on the shelf.
- Small size for easy installation in virtually any generator terminal box.



- ⚠ Phase rotation A-B-C
- 🛕 Item not supplied by Basler Electric Co.
- If remote voltage adjust is not used, short terminals 6 and 7
- A Short terminals 50 and COM together for 50 Hz operation. Leave unconnected for 60 Hz operation.
- The secondary winding of a sensing transformer must be grounded as closely to the transformer as practical. When interconnecting more than one transformer, ensure that the secondary winding of only one transformer is grounded.

Figure 1 - DECS-150 Connection Diagram for a Typical Application



## AVC63-7, AVC63-7D, AVC63-7F Voltage Regulators

### **Specifications**

#### Input Power (1-phase)

Voltage Range: 170 to 305 Vac Frequency: 50/60 Hz

Burden: 900 VA max at 240 Vac

#### Sensing Input (1-phase)

Voltage Range:

AVC63-7: 170 to 264 Vac AVC63-7F: 380 to 480 Vac Frequency: 50/60 Hz Burden: 5 VA

**Output Power** 

 $\begin{array}{ll} \text{Max Continuous:} & 7 \text{ Adc at 63 Vdc} \\ \text{Field Resistance:} & 9 \Omega \text{ minimum} \end{array}$ 

#### **Voltage Adjust Range**

Internal Adjust:

AVC63-7: 170 to 264 Vac AVC63-7F: 340 to 528 Vac

External Adjust: ±10% of nominal internal

adjust value

#### **Regulation Accuracy**

Better than ±0.25% no-load to full-load

#### **Voltage Drift**

<±1% voltage variation for a 50°C (122°F) change

#### **Response Time**

<16 ms

#### **Frequency Compensation**

See Figure 2.

#### Voltage Buildup

Automatic voltage buildup occurs for residual generator voltages as low as 6 Vac at 25 Hz.

#### **Power Dissipation**

35 W maximum

#### **Paralleling Provisions**

Input for 5 A CT with 2.5 VA input burden.
Adjustable droop from 0 to 6% at 0.8 power factor




Figure 2 - Frequency Compensation Curves

# Basler Electric

Highland, Illinois USA Tel +1 618.654.2341 Fax +1 618.654.2351 email: info@basler.com Suzhou, P.R.China Tel +86.512.8227.2888 Fax +86.512.8227.2887 e-mail: chinainfo@basler.com

#### **Agency/Certifications**

CSA certified, UL 6200:2019 recognized, China RoHS compliant

#### Environmental

Operating Temp: -40°C to 60°C (-40°F to 140°F)
Storage Temp: -65°C to 85°C (-85°F to 185°F)
Shock: 15 G in three perpendicular

planes

Vibration:

5 to 26 Hz: 1.2 G

27 to 53 Hz: 0.036" double amplitude

54 to 1,000 Hz: 5 G

**Physical** 

Weight: 17 oz (482 g)

Dimensions (WxHxD):

5.52 x 4.92 x 2.98 inches (138 x 123 x 75 mm)

For complete specifications, download the instruction manual at www.basler.com.

#### **Related Products**

**AVC63 Series Voltage Regulators** provide the performance and functionality that revolutionized the modern analog voltage regulator market.

- AVC63-4, AVC63-4D
- AVC63-12

#### **BE1-FLEX Protection, Automation and Control System**

Designed to be configurable for nearly any Power System Application.

#### **ES Series Protection Relays**

Provide a wide variety of cost-saving options to simplify industrial application protection.

#### **DECS-150 Digital Excitation Control System**

Provides precise voltage regulation, exceptional system response, and valuable protection of the generator and excitation system. Ideal for distributed generation, cogeneration, and peak shaving applications.

#### **DECS-250 Digital Excitation Control System**

Provides precise voltage, var and Power Factor regulation, and exceptional system response, plus generator and motor protection.

#### **DGC-2020 Digital Genset Controller**

An advanced genset control system with extensive functionality and flexibility.

#### **DGC-2020ES Digital Genset Controller**

The total system solution for emergency and stand alone generator set applications.

#### **DGC-2020HD Digital Genset Controller**

An advanced, but rugged genset control system designed for paralleling and complex load sharing schemes.

